






linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



PCB LAYOUT



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	25.04.27

UL/CUL 技术 参数				
UL/CUL Technical Data				
等 级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	-	-
额定电流	Rated Current [A]	20	-	-
接线范围	Wire Range	22-12		
单/多芯线	Solid/Stranded [AWG]			
IEC 技术参数				
IEC Technical Data				
额定电压	Rated Voltage [V]	450		
额定电流	Rated Current [A]	32		
耐电压	Withstanding Voltage	AC2500V/1Min		
导线截面积	Conductor cross section	4.0		
硬质/柔性导线	Solid/ flexible [mm²]			
材 料				
绝缘材料	Insulation Material	PA66		
阻燃等级	Imflammability	UL94V-0		
导体材料	Contacto Material	铜合金 Copper alloy		
导体表面镀层	Contactive Coating	镀锡 Tin plating		
一般参数 Other Data				
间距 Pitch	[mm]	8.25		
极数 Poles	[P]	2-24		
剥线长度 Stripping Length	[mm]	-		
螺丝 Screw/ 扭矩 Torque(Max)	[N.m]	M3/0.8		
工作温度 Operating temperatur	[°C]	-40~+105		
引针尺寸 Pin Dimensions	[mm]	4.0		
PCB板孔径 PCB Hole Diameter	[mm]	1.5		

DES.	FGG	DATE	25.04.27
CHK.	CLF	DATE	25.04.27
APP.	CLF	DATE	25.04.27

单位 / UNITS mm 尺寸 / SIZE A4 比例 / SCALE 1:1

YIHENTRA
TECHNICAL DRAWING

第三视角/THIRD ANGLE PROJECTION		版本 / REV	A
		名称 / TITLE	HB825-8.25