





linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



PCB Layout



Px2.54+2.54



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	21.10.12

UL/CUL 技术参数				
UL/CUL Technical Data				
等 级	Use Group	B	C	D
额定电压	Rated Voltage [V]	150	-	-
额定电流	Rated Current [A]	2	-	-
接线范围	Wire Range	26-20		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	AC1300V/1Min		
IEC 技术参数				
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	63	160	320
额定电流	Rated Current [A]	2	2	2
额定冲击电压	Impulse withstand voltagea [KV]	2.5	2.5	2.5
导线截面积	Conductor cross section	0.5		
硬质/柔性导线	Solid/ flexible [mm²]			
材 料 Material				
绝缘材料	Insulation Material	热塑性材料/Thermoplastic		
导体材料	Contactar Material	铜合金 Copper alloy		
导体表面镀层	Contactive Coating	镀锡 Tin Plated		
一般参数 Other Data				
间距 Pitch	[mm]	2.54		
极数 Poles	[P]	01~XX		
剥线长度 Stripping Length	[mm]	11.0		
螺丝 Screw/扭矩 Torque(Max)	[N.m]	-		
工作温度 Operating temperatur	[°C]	-40~+105		
引针尺寸 Pin Dimensions	[mm]	3.50		
PCB板孔径 PCB Hole Diameter	[mm]	1.20		
安装类型 Mounting type		波峰焊/Wave soldering		

DES.	SJD	DATE	21.10.12
CHK.	BY	DATE	21.10.12
APP.	CLF	DATE	21.10.12

单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	1:1
------------	----	-----------	----	------------	-----

YIHENTRA
TECHNICAL DRAWING

第三视角 / THIRD ANGLE PROJECTION	版本 / REV	A
-------------------------------	----------	---

名称 / TITLE	KF141R-2.54
------------	-------------